



## MOB-7401 PUR polyurethane based

■ MaxTiger Moisture Barrier MOB 7401 / PUR is one component, solvent, polyurethane based, moisture reducing impregnation primer.

### ■ Place of Use

Concrete, brick, stone, ceramic, marble, compacted concrete, sheet metal, untreated wood, such as porous and absorbent used on surfaces MaxTiger Moisture Barrier MOB 7401 / PUR PMT is compatible with polyurethane based systems.

### ■ Product Typification

Colour	: Yellowish transparent
Density (20 °C, gr / cm <sup>3</sup> )	: 1,0-1,05 Solid : Min. 40%
Quantity of paper	: The original packaging should be opened after opening
Initial drying (20 °C, hour)	: 1-1,5 hour
Hardening time (Hours)	: 6-8 hour
Ambient and ground temperature	: Application ambient temperature should not be below + 10° C and above +30° C
Waiting time between coats	: Minimum 3 hours at +10 ° C; Maximum 12 hours +25 ° C Minimum 1 hour Maximum 12 hours.

### ■ Application

MaxTiger Moisture Barrier MOB 7401 / PUR PMT applications should be free of oil, wax, grease, water repellents, dust, free-standing tube and concrete curing material. Foaming occurs due to the carbon dioxide output generated by the very thickness. So it is very thin and will not create film on the surface. Depending on the absorbency of the surface and the waiting times between the layers has added a lot.

### ■ Limitations

MOB 7401 / PUR - PMT surface temperature +5 °C is applied on the surface.

Sale of opened packages.

MOB 7401 / PUR - PMT application; Protect from direct water contact for at least 8 hours.

With hydrostatic pressure, do not apply water and water to the surface or on wet surfaces. First cut off this water supply.

### ■ Security Precautions

Contains flammable solvent. Do not approach with fire.

Wear safety glasses and gloves

Do not expose to continuous steam.

Avoid frequent contact with skin.

In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.

Provide good ventilation in confined areas.

In case of contact with skin, clean with alcohol first; then wash with plenty of soapy water.

Wash your hands before eating anything.

Do not smoke when indoors.

### ■ Use Time

If the lid is left open, it reacts with the humidity of the air and starts to harden from the surface.

They must be used after the packaging is opened.

